

Number of contacts

2+

40 A 830 V 6 kV 3

| Identification | Conductor cross-section (mm ²) | Part number | | Drawing (dimensions in mm) | | | | | | | | | | | | | | | | | | |
|---|--|--|--|--|-------------------------|---|------------------|----------------------------|---------|--------|----------------------------|---------|--------|--------------------------|---------|--------|--------------------------|--------|--------|--------------------------|--------|-------|
| | | Male | Female | | | | | | | | | | | | | | | | | | | |
| <p>Han® Q, 2/0 High Voltage, Crimp termination, Pack contents: With heat shrink tube</p> <p>Please order crimp contacts separately.</p> | 1.5 ... 10 | 09 12 002 3052 | 09 12 002 3152 | <p>Contact arrangement (view from termination side)</p> | | | | | | | | | | | | | | | | | | |
| <p>Han® C, Crimp contact, Contact surface: Silver plated</p> | 1.5 2.5 4 6 10 | 09 32 000 6104 09 32 000 6105 09 32 000 6107 09 32 000 6108 09 32 000 6109 | 09 32 000 6204 09 32 000 6205 09 32 000 6207 09 32 000 6208 09 32 000 6209 | <table border="1"> <thead> <tr> <th>Conductor cross-section</th> <th>Ø</th> <th>Stripping length</th> </tr> </thead> <tbody> <tr> <td>1.5 mm² AWG 16</td> <td>1.75 mm</td> <td>9.5 mm</td> </tr> <tr> <td>2.5 mm² AWG 14</td> <td>2.25 mm</td> <td>9.5 mm</td> </tr> <tr> <td>4 mm² AWG 12</td> <td>2.85 mm</td> <td>9.5 mm</td> </tr> <tr> <td>6 mm² AWG 10</td> <td>3.5 mm</td> <td>9.5 mm</td> </tr> <tr> <td>10 mm² AWG 8</td> <td>4.3 mm</td> <td>12 mm</td> </tr> </tbody> </table> | Conductor cross-section | Ø | Stripping length | 1.5 mm ² AWG 16 | 1.75 mm | 9.5 mm | 2.5 mm ² AWG 14 | 2.25 mm | 9.5 mm | 4 mm ² AWG 12 | 2.85 mm | 9.5 mm | 6 mm ² AWG 10 | 3.5 mm | 9.5 mm | 10 mm ² AWG 8 | 4.3 mm | 12 mm |
| Conductor cross-section | Ø | Stripping length | | | | | | | | | | | | | | | | | | | | |
| 1.5 mm ² AWG 16 | 1.75 mm | 9.5 mm | | | | | | | | | | | | | | | | | | | | |
| 2.5 mm ² AWG 14 | 2.25 mm | 9.5 mm | | | | | | | | | | | | | | | | | | | | |
| 4 mm ² AWG 12 | 2.85 mm | 9.5 mm | | | | | | | | | | | | | | | | | | | | |
| 6 mm ² AWG 10 | 3.5 mm | 9.5 mm | | | | | | | | | | | | | | | | | | | | |
| 10 mm ² AWG 8 | 4.3 mm | 12 mm | | | | | | | | | | | | | | | | | | | | |
| <p>Coding element</p> | | 09 12 000 9922 | | | | | | | | | | | | | | | | | | | | |