

## Technical characteristics

Contact resistance	≤1 mΩ
Material (contacts)	Copper alloy
RoHS	compliant with exemption

## Specifications and approvals





EN 60664-1  
IEC 61984

## Details

**Crimping tools** see chapter Han 90

### Remarks on the crimp technique

The wire gauges mentioned in the catalogue refer to geometric wire gauges of cables.

Identification	Conductor cross-section (mm <sup>2</sup> )	Part number		Drawing (dimensions in mm)																														
		Male	Female																															
Han E®, Crimp contact, Contact surface: Silver plated  	0.5	09 33 000 6121	09 33 000 6220	 <table border="1" data-bbox="965 1115 1412 1406"> <thead> <tr> <th>Conductor cross-section</th> <th>Identification</th> </tr> </thead> <tbody> <tr> <td>0.14-0.37 mm<sup>2</sup> AWG 26-22</td> <td>no groove</td> </tr> <tr> <td>0.5 mm<sup>2</sup> AWG 20</td> <td>no groove</td> </tr> <tr> <td>0.75 mm<sup>2</sup> AWG 18</td> <td>1 groove*</td> </tr> <tr> <td>1 mm<sup>2</sup> AWG 18</td> <td>1 groove</td> </tr> <tr> <td>1.5 mm<sup>2</sup> AWG 16</td> <td>2 groove</td> </tr> <tr> <td>2.5 mm<sup>2</sup> AWG 14</td> <td>3 groove</td> </tr> <tr> <td>3 mm<sup>2</sup> AWG 12</td> <td>wide groove</td> </tr> <tr> <td>4 mm<sup>2</sup> AWG 12</td> <td>no groove</td> </tr> </tbody> </table> <p>* on the back crimp collar</p> <p>Stripping length 7.5 mm</p>  <table border="1" data-bbox="965 1568 1412 1680"> <thead> <tr> <th>Conductor cross-section</th> <th>∅</th> <th>Stripping length</th> </tr> </thead> <tbody> <tr> <td>0.75-1 mm<sup>2</sup> AWG 18</td> <td>1.45 mm</td> <td>7.5 mm</td> </tr> <tr> <td>1.5 mm<sup>2</sup> AWG 16</td> <td>1.75 mm</td> <td>7.5 mm</td> </tr> <tr> <td>2.5 mm<sup>2</sup> AWG 14</td> <td>2.25 mm</td> <td>7.5 mm</td> </tr> </tbody> </table>	Conductor cross-section	Identification	0.14-0.37 mm <sup>2</sup> AWG 26-22	no groove	0.5 mm <sup>2</sup> AWG 20	no groove	0.75 mm <sup>2</sup> AWG 18	1 groove*	1 mm <sup>2</sup> AWG 18	1 groove	1.5 mm <sup>2</sup> AWG 16	2 groove	2.5 mm <sup>2</sup> AWG 14	3 groove	3 mm <sup>2</sup> AWG 12	wide groove	4 mm <sup>2</sup> AWG 12	no groove	Conductor cross-section	∅	Stripping length	0.75-1 mm <sup>2</sup> AWG 18	1.45 mm	7.5 mm	1.5 mm <sup>2</sup> AWG 16	1.75 mm	7.5 mm	2.5 mm <sup>2</sup> AWG 14	2.25 mm	7.5 mm
	Conductor cross-section	Identification																																
	0.14-0.37 mm <sup>2</sup> AWG 26-22	no groove																																
	0.5 mm <sup>2</sup> AWG 20	no groove																																
	0.75 mm <sup>2</sup> AWG 18	1 groove*																																
	1 mm <sup>2</sup> AWG 18	1 groove																																
	1.5 mm <sup>2</sup> AWG 16	2 groove																																
	2.5 mm <sup>2</sup> AWG 14	3 groove																																
	3 mm <sup>2</sup> AWG 12	wide groove																																
	4 mm <sup>2</sup> AWG 12	no groove																																
Conductor cross-section	∅	Stripping length																																
0.75-1 mm <sup>2</sup> AWG 18	1.45 mm	7.5 mm																																
1.5 mm <sup>2</sup> AWG 16	1.75 mm	7.5 mm																																
2.5 mm <sup>2</sup> AWG 14	2.25 mm	7.5 mm																																
0.75	09 33 000 6114	09 33 000 6214																																
1	09 33 000 6105	09 33 000 6205																																
1.5	09 33 000 6104	09 33 000 6204																																
2.5	09 33 000 6102	09 33 000 6202																																
3	09 33 000 6106	09 33 000 6206																																
4	09 33 000 6107	09 33 000 6207																																
Han E®, Crimp contact, Relay contact, Contact surface: Silver plated  	0.75 ... 1	09 33 000 6109																																
	1.5	09 33 000 6110																																
	2.5	09 33 000 6111																																