

Han
Eco

Optical modules		Han® SC module	Han® Multi module	Han® Multi module
	Number of contacts	4	4	12*
	Male module (M)	09 14 004 4701	09 14 004 4501	09 14 012 4501
	Female module (F)	09 14 004 4713	09 14 004 4512	09 14 012 4512
	Contacts			
	1 mm POF	20 10 001 5211	Male: 20 10 001 4211 Female: 20 10 001 4221	Male: 20 10 001 4211 Female: 20 10 001 4221
	1 mm POF Fast assembly termination	20 10 001 5217		
	SI-Fibre 200 / 230 µm Multi-Mode	20 10 230 5211	Male: 20 10 230 4211 Female: 20 10 230 4221	Male: 20 10 230 4211 Female: 20 10 230 4221
	GI-Fibre 50-62.5 / 125 µm Multi-Mode	20 10 125 5211	Male: 20 10 125 4212 Female: 20 10 125 4222	Male: 20 10 125 4212 Female: 20 10 125 4222

Special modules		Han-Eco® PE module	Han® Dummy module
	Field of application	for Han-Eco® hoods/housings only	to fill-up empty module places
	Number of contacts	1 x PE	
	Electrical data		
	Cross-section	1.5 ... 16 mm²	
	Termination type	Screw termination	
	Male module (M)	19 41 001 2600	09 14 000 9950
	Female module (F)	19 41 001 2700	

* Double module, requires two places in the frame

Monoblocks		6 B	10 B	16 B	24 B
	Number of contacts	10	14	20	28
	Electrical data	16 A / 500 V	16 A / 500 V	16 A / 500 V	16 A / 500 V
	Cross section	0.75 ... 2.5 mm²	0.75 ... 2.5 mm²	0.75 ... 2.5 mm²	0.75 ... 2.5 mm²
	Termination type	Screw termination	Screw termination	Screw termination	Screw termination
	Male	19 41 010 2601	19 41 014 2601	19 41 020 2601	19 41 028 2601
	Female	19 41 010 2701	19 41 014 2701	19 41 020 2701	19 41 028 2701