Number of contacts

max. 96, 48



Female connectors

Identification	No. of contacts	Part number	Drawing	Dimensions in mm
Female connector for crimp contacts			(2 : 1)	
Order contacts separately				
Type C	96	09 03 096 3214[f)] 09 03 596 3214[c)f)]		
Type C	96	09 03 096 3217[f)]		
Position marking turned for mating type R male				



Identification	Part number	Performance levels according to IEC 60603-2. Explanation chapter 00	
		2	1
Female crimp contacts BC			
Bandoliered contacts (approx. 5,000 pieces)		09 02 000 6484	09 02 000 6474
Bandoliered contacts (approx. 500 pieces)		09 02 000 8434	09 02 000 8444
Individual contacts[1)]		09 02 000 8484	09 02 000 8474

Wire gauge mm²	AWG	Insulation ø mm
0.09 - 0.5	28 - 20	0.7 - 1.5

3.5 + 0.5 mm of insulation is stripped from the wires to be crimped

For the fabrication in line with the specification please use exclusively crimp tools approved by HARTING (see DIN EN 60352-2)

Insertion, removal and crimping tools see chapter 30

Bandoliered contacts



Individual contacts

[c)] Connectors with coding see chapter 00
[1)] Packaging unit 1,000 pieces
[f)] Railway classification NFF 16-101, Smoke index: F1, Flammability class: I2