

Identification	Part No.	Drawing	Dimensions in mm
<p>Han® PushPull Signal panel feed-through HIFF to hold the 10-poles insert</p>		<p>Ground contacts</p>	<p>PANEL CUT: 2x M3 4x Max R1,25 22,8±0,1 33±0,1 19,2±0,1</p>
<p>Metal rectangular</p>	<p>09 35 012 0311</p>	<p>V14 metal rectangular housing HIFF insert Flat seal (32,75)</p>	<p>(22,2) (42)</p>
<p>Metal circular</p>	<p>09 35 012 0312</p>	<p>V14 metal circular housing Ground contact (x2) HIFF adapter M28 x1,5 Flat seal (32,75)</p>	<p>PANEL CUT: 11,8±0,1 Ø28±0,1 Thickness panel: 1mm to 6mm. Nut screwing torque: 2.5 to 3N.m.</p>
<p>Metal circular</p>	<p>09 35 012 0312</p>	<p>V14 metal circular housing Ground contact (x2) HIFF adapter M28 x1,5 metal nut Flat seal (32,75)</p>	<p>Ø30</p>
<p>Plastic rectangular</p>	<p>09 35 012 0331</p>	<p>V14 plastic rectangular housing Flat seal</p>	<p>Panel cut out (22,2) (42) 2x M3 4x Max R1,25 22,8±0,1 33±0,1 19,2±0,1</p>
<p>Plastic rectangular</p>	<p>09 35 012 0331</p>	<p>V14 plastic rectangular housing Flat seal</p>	<p>Panel cut out (22,2) (42) 2x M3 4x Max R1,25 22,8±0,1 33±0,1 19,2±0,1</p>
<p>Han® PushPull Signal solder jack angled</p>	<p>09 35 002 6001</p>	<p>(24,5) 20±0,2 3 2x 3 (±6) 6</p>	<p>2x 3 (±6) 3 15,75±0,1 2,4 2,4 3x 3 (±6) 15,6±0,1</p>
<p>Han® PushPull Signal solder jack straight</p>	<p>09 35 002 6002</p>	<p>19,4±0,2 A 124±0,5 15,5±0,1</p>	<p>13,95±0,1 1,8±0,05</p>
<p>suitable housings, bulkhead mounting</p>	<p>09 35 002 6002</p>	<p>19,4±0,2 A 124±0,5 15,5±0,1</p>	<p>13,95±0,1 1,8±0,05</p>
<p>Metal</p>	<p>09 35 002 0303</p>	<p>19,4±0,2 A 124±0,5 15,5±0,1</p>	<p>13,95±0,1 1,8±0,05</p>
<p>Plastic</p>	<p>09 35 002 0323</p>	<p>19,4±0,2 A 124±0,5 15,5±0,1</p>	<p>13,95±0,1 1,8±0,05</p>