PushPull RJ45 IP65/IP67 connectors



3



HARTING PushPull acc. to IEC 61 076-3-106 variant 4

Housing bulkhead mounting and housing cable-to-cable combinations Advantages Technical characteristics

/ availages			
 Type / Material Category Number of wires 	RJ45 plastic 5 / 6 _A 4 / 8	Connector type	HARTING PushPull (V4) RJ45 connector acc. to IEC 61 076-3-106 variant 4
Termination Outer diameter	478 IDC 5 - 9 mm	Number of contacts Transmission performance	4 or 8 depending on type Category 5 / 6 _A depending on type
Application • Industrial cabling • On machines and control units • Outdoor		Transmission rate	10/100 Mbit/s 1/ 10 Gbit/s depending on type fully shielded, 360° shielding contact
• HARTING PushPull technology		Cable termination	tool-less with IDC contacts or preLink [®] IDC
 Compact design High packing density Device integration via RJ45 PCB connectors 		Degree of protection Temperature range	IP65/IP67 -40 °C +70 °C
		Housing material	polycarbonate, UL 94 V0, black

Identification Part number Drawing Dimensions in mm HARTING PushPull V4 max.32,3 (1)25,2 Housing bulkhead mounting A Housing bulkhead mounting -₽₽ Compact with integrated seal, mounting drills for M2.5 plastic, black 09 45 545 0028 Housing bulkhead mounting – EasyInstall with integrated seal, mounting drills for M3 plastic, black $| \oplus |$ (Not combinable with (3)!) 09 45 545 0032 14. Sanata ax. 3 €) axis

03

62